



# TS101 Plus 4G EV -Vidyut

Parameters		Specifications
Cellular	LTE-Cat1	B1, B3, B5, B8, B34, B39, B40, B41
	2G	900/1800 MHz
Communication Interface		TCP/IP
Short Range	BLE	5.0
Navigation	GNSS	GPS, GLONASS, BeiDou
External Interfaces	Digital Input	5 Nos
	Digital Output	4 Nos
	Analog Input	2 Nos
	RS232	1 No
	RS485	1 No
	CAN	1 No
	1 Wire	1 No
Wake-up Sources	USB	2.0 (For Config Purpose Only)
	IGN	Yes
	Panic Button	Yes
	Main Power	Yes
Device Case Open / Tamper Alert		Yes
LED Status Indicators		GNSS, Process, GSM, Power
Power Supply		9-90V DC
Sleep Mode Current		<5mA
Internal Battery		850mAh
LTE / GNSS / BLE Antenna		Internal
Movement Sensors		Accelerometer & Gyroscope
SIM		Plastic (4FF - Nano)
Data Storage		128 MByte
Internal Data Storage		40000 Records
Configuration		USB / SMS / TCPIP / BT
OTA / FOTA		Yes



CAN Available



9 - 90V Support



9 Digital I/Os  
2 Analog Inputs



Accelerometer & Gyroscope



Internal Storage Data  
Capacity Of 40000 Records



Low power consumption &  
power optimization



Remote Health Checking /  
Diagnostics Through SMS



Easy Installation and  
Configuration



IP65 Rating

Contact us at:

Web: [www.itriangle.in](http://www.itriangle.in)

✉ : [sales@itriangle.in](mailto:sales@itriangle.in)

☎ : +91 9739974445

**Note:**

*We pursue a policy of continuous research & product development. Specifications and features are subject to change without prior notice.*

\* Backup time may vary based on configuration and battery ageing



CAN Available



9 - 90V Support

9 Digital I/Os  
2 Analog Inputs

Accelerometer &amp; Gyroscope

Internal Storage Data  
Capacity Of 40000 RecordsLow power consumption &  
power optimizationRemote Health Checking /  
Diagnostics Through SMSEasy Installation and  
Configuration

IP65 Rating

# TS101 Plus 4G EV -Vidyut

Parameters	Specifications	
Temperature	Operating Temperature (Without Battery)	-25 to +85 deg
	Storage Temperature (Without Battery)	-40 to +85 deg
	Operating Humidity	5% to 95% non-condensing
	Battery Charge Temperature	-0 to +45 deg
	Battery Discharge Temperature	-20 to +60 deg
	Battery Storage Temperature	-20 to +45 deg for 1 month -20 to +35 deg for 6 month
Performance & Durability	Vibration	IS:9000-8
	Ingress Protection	IP65
	Dry Heat	IS:9000 -3
	Shock	IS:9000-7
	Electrical (Load Dump)	ISO7637-2
	EMI / EMC	AIS004-3
Dimensions	97mm x 84mm x 31mm	
Weight	~170 grams	

Contact us at:

Web: [www.itriangle.in](http://www.itriangle.in)✉ : [sales@itriangle.in](mailto:sales@itriangle.in)

☎ : +91 9739974445

**Note:**

*We pursue a policy of continuous research & product development. Specifications and features are subject to change without prior notice.*

\* Backup time may vary based on configuration and battery ageing